

ACCESS POINT GRADES AND APRON LENGTHS FOR ROADWAYS AND DRIVEWAYS

DESIGN VALUES				
ROADWAY	APRON LENGTH	GRADE CHANGE (D)		
CLASSIFICATION	(A)	DESIRABLE	MAXIMUM	
ARTERIAL	MIN. 20 FEET	4% OR LESS	5%	
COLLECTOR	MIN. 15 FEET	5% OR LESS	6%	
LOCAL ACCESS	MIN. 10 FEET	6% OR LESS	7%	

AccessGrades.doc



SKAGIT COUNTY **DEPARTMENT OF PUBLIC WORKS**

REVISIONS	DATE	

ROADWAY STANDARDS

GENERAL NOTES

- 1. PIVOT POINT SHALL BE AT THE EDGE OF SHOULDER
- 2. DESIRABLE WIDTHS SHOWN WILL BE THE REQUIREMENT. UNLESS THE APPLICANT DEMONSTRATES TO THE **ENGINEER'S SATISFACTION THAT** THEY CANNOT BE OBTAINED.
- 3. VERTICAL CURVES ARE NOT TO EXCEED A 3-1/4" HUMP OR A 2" DEPRESSION IN A 10 FOOT CHORD.
- 4. IN CASES OF FUTURE LAND WIDEN-ING AND ADDITIONAL LANES. THE APRON LENGTH SHALL BE INCREASED TO ACCOMMODATE FUTURE WIDENING.

ACCESS POINT GRADES FIGURE C-4

6/26/2000