



# SKAGIT COUNTY PARKS & RECREATION SWINOMISH CHANNEL BOAT LAUNCH RENOVATION





DWG NO.	SHT. NO.	SHEET TITLE							
	GENERAL								
G1.0	1	LOCATION MAP, VICINITY MAP, AND SHEET INDEX							
G1.1	2	ABBREVIATIONS AND SYMBOLS							
G1.2	3	GENERAL NOTES							
G1.3	4	SPECIAL INSPECTION SCHEDULE							
		CIVIL							
C1.0	5	EXISTING CONDITIONS PLAN							
C1.1	6	TEMPORARY EROSION/SEDIMENTATION CONTROL PLAN AND NOTES							
C1.2	7	DEMOLITION PLAN, SECTION AND NOTES							
C2.0	8	PROPOSED CONDITIONS PLAN AND PROFILE							
		STRUCTURAL							
S1.0	9	STEEL FRAME FLOAT							
S1.1	10	STEEL FRAME FLOAT WITH INTERNAL PILE							
S1.2	11	BULLRAIL AND HINGE DETAILS							

# CIVIL/STRUCTURAL ENGINEER

REID MIDDLETON, INC 728 134TH ST SW, SUITE 200 EVERETT WA 98204 CONTACT: WILLY AHN PHONE: 425-741-3800

# **OWNER**


SKAGIT COUNTY PARKS & RECREATION ADDRESS: 1730 CONTINENTAL PLACE, MOUNT VERNON, WA 98273 CONTACT: BRIAN ADAMS PHONE: 360-416-1356

# PROJECT SITE ADDRESS

BOAT LAUNCH ROAD, LA CONNER, WA 98257 SECTION 11, TOWNSHIP 34 NORTH, RANGE 2 EAST LATITUDE: 48° 27' 16.60" N LONGITUDE: 122° 30' 47.35" W

# 100% SUBMITTAL

pl		REVISIONS		DESIGNED BY:   J. STRUB			
4:42pm	NO.	DATE	BY	DESCRIPTION	APP'D	DRAWN BY:	
1:42						D. OLSEN	
2 –						CHECKED BY: W. AHN	
202						DATE:	
22,						05/23/25	
Мау						PROJECT NO: 24-22-006	



HORIZ NO SCALE IF "L" DOES NOT MEASURE 1" ADJUST SCALES ACCORDINGLY



728 134th Street SW · Suite 200 Ph: 425 741-3800

SKAGIT COUNTY PARKS & RECREATION SWINOMISH CHANNEL BOAT LAUNCH RENOVATION

SHEET TITLE: LOCATION MAP, VICINITY MAP, AND SHEET INDEX **G1.0** 

# **TITLES**

ADDIVENIATIONS							
AASHT0	AMERICAN ASSOCIATION OF	Е	EAST	М	METER	SST	STAINLESS STEEL
	STATE HIGHWAY OFFICIALS	EA	EACH	MATL	MATERIAL	SOG	SLAB ON GRADE
AB	ANCHOR BOLT	EF	EACH FACE	MAX	MAXIMUM	SPC	SPACE(ED)(ING)
ABAND	ABANDONED	EHW	EXTREME HIGH WATER	MB	MAILBOX	SPEC(S)	SPECIFICATION(S)
ABUT	ABUTMENT	EJ	EXPANSION JOINT	MECH	MECHANICAL	SQ SS	SQUARE
ACI	AMERICAN CONCRETE	EL, ELEV	ELEVATION	MFR(S)	MANUFACTURER(S)	SS	SANITARY SEWER
ADDI	INSTITUTE	ELB	ELBOW	MH	MANHOLE	SSMH	SANITARY SEWER MANHOLE
ADDL	ADDITIONAL	EMB	EMBANKMENT	MHW	MEAN HIGH WATER	ST	STREET
ADJ AISC	ADJUST, ADJACENT AMERICAN INSTITUTE OF	EMBED ENGR	EMBEDMENT ENGINEER	MHHW MIC	MEAN HIGHER HIGH WATER MONUMENT IN CASE	STA STD	STATION STANDARD
AISC	STEEL CONSTRUCTION	EOA	EDGE OF ASPHALT	MIN	MINIMUM	STIFF	STIFFENER
ALIGN	ALIGNMENT	EOC	EDGE OF CONCRETE	MISC	MISCELLANEOUS	STIR	STIRRUP
ALT	ALTERNATE	EOD	EDGE OF DIRT	MJ	MECHANICAL JOINT	STPS	STEPS
ANCH	ANCHOR	EOG	EDGE OF GRAVEL	MLW	MEAN LOW WATER	STL	STEEL
AP	ANGLE POINT	EP	EDGE OF PAVEMENT	MLLW	MEAN LOWER LOW WATER	STRUC	STRUCTURAL
APPROX	APPROXIMATELY	EQ	EQUAL	M/L	MONUMENT LINE	SUPP	SUPPORT
APWA	AMERICAN PUBLIC	EQUIP	EQUIPMENT	MON	MONUMENT	SW	SOUTHWEST
. =	WORKS ASSOCIATION	ETC	ETCETERA	MUTCD	MANUAL ON UNIFORM TR	S/W	SIDEWALK
ARCH	ARCHITECT, ARCHITECTURAL	EW	EACH WAY		CONTROL DEVICES	SYM	SYMMETRICAL, SYMBOL
ARV	AIR RELIEF VALVE	EXC	EXCAVATION	N1	NODTH	TD	TUDUCT DI COIX
ASPH ASTM	ASPHALT AMERICAN SOCIETY FOR	EXIST EXP	EXISTING EXPANSION	N NE	NORTH NORTHEAST	TB TAN	THRUST BLOCK TANGENT
ASTM	TESTING AND MATERIALS	EXT	EXTERIOR, EXTENSION	NEG	NEGATIVE	T&B	TOP & BOTTOM
AVE	AVENUE	LXI	EXTRUDED	NEMA	NATIONAL ELECTRICAL	TBM	TEMPORARY BENCH MARK
AVG	AVERAGE	EVT	EVERETT	1451417	MANUFACTURERS ASSOC	TD	TRENCH DRAIN
				NIC	NOT IN CONTRACT	TEL	TELEPHONE
BLDG	BUILDING	FDN	FOUNDATION	NOM	NOMINAL	TEMP	TEMPORARY
BLK	BLOCK, BLOCKING	FLG	FLANGE	NTS	NOT TO SCALE	THK	THICK(NESS)
BLVD	BOULEVARD	FF	FAR FACE, FINISH FLOOR	No.	NUMBER	THRU	THROÙGH
BOC	BACK OF CURB	FG	FINISH GRADE	NW	NORTHWEST	TMH	TELEPHONE MANHOLE
BOW	BACK OF WALK	FH	FIRE HYDRANT		011 051755	TOC	TOP OF CURB
BOL	BOLLARD	FIG	FIGURE	20	ON CENTER	TOE	CONCAVE SLOPE BREAK
BM	BEAM, BENCH MARK	FIN FLR	FINISH, FINISHED	OD OHW	OUTSIDE DIAMETER ORDINARY HIGH WATER	TOP TOPO	CONVEX SLOPE BREAK
BNSF	BURLINGTON NORTHERN SANTA FE	FLR FM	FLOOR FORCE MAIN	OHW OPNG	OPENING	TOPO TOT	TOPOGRAPHY TOTAL
BOT	BOTTOM	FNC	FENCE	OPP	OPPOSITE	TOW	TOP OF WALL
BRDG	BRIDGE	FOC	FACE OF CURB	OT	OVERHEAD TELEPHONE	TP	TEST PIT
BRG	BEARING	FOW	FACE OF WALL	•		TRAN	TRANSITION
BRK	BREAK	FT	FEET/FOOT	Р	POLE, POWER	TRANSV	TRANSVERSE
BTWN	BETWEEN	FTG	FOOTING	PAR	PARALLEL	TR	TELEPHONE RISER
				PC	PRECAST	TUN	TUNNEL
C	CAMBER, CHANNEL	G	GAS LINE	PCF	POUNDS PER CUBIC FOOT	TV	TELEVISION
CAL	CALIPER	GA	GAUGE	PEN	PENETRATION	TWST	TWISTED
CANT	CANTILEVER	GAL	GALLON	PED	PEDESTRIAN	TYP	TYPICAL
CB CB1	CATCH BASIN TYPE 1	GALV	GALVANIZED	PERP	PERPENDICULAR	UHMW	LILTDA LICH MOLECHIAD WEIGHT
CB1 CB2	CATCH BASIN TYPE 1 CATCH BASIN TYPE 2	GB GE	GRADE BREAK GRATE ELEVATION	PI PL, PL	POINT OF INTERSECTION PLATE	UG	ULTRA HIGH MOLECULAR WEIGHT UNDERGROUND
CF	CUBIC FEET	GEN	GENERAL	PNL	PANEL	UP	UTILITY POLE
CG	CURB & GUTTER	GM	GAS METER	POC	POINT OF CONNECTION	UPA	UTILITY POLE ANCHOR
COG	CENTER OF GRAVITY	GR	GUARD RAIL	PROP	PROPERTY	UTIL	UTILITY
CI	CAST IRON	GRD	GRADE	PRV	PRESSURE REDUCING VALVE	V	
CICL	CAST IRON CONCRETE	GRND	GROUND	PS	PRESTRESS		VALVE
	LINED	GV	GAS VALVE	PSF	POUNDS PER SQUARE FOOT	VAR	VARIES
CIP	CAST IN PLACE			PSI	POUNDS PER SQUARE INCH	VFRT	VERTICAL

PS PSF PSI

RC

RD

REF

RR RT

SB

SCHED SD

SERV

SHLDR

PAVEMENT

QUANTITY

REINF CONC

ROOF DRAIN

REFERENCE

REQUIRED

RETAINING

RAILROAD RIGHT

RETAINING WALL

RIGHT OF WAY

SOUTH, SLOPE

SOIL BORING

STORM DRAIN

STORM DRAIN MANHOLE

SPOT EL/ SOUTHEAST

SCHEDULE

SECTION

SERVICE SHOULDER

SHEET

SIMILAR

SURVEY LINE

RIGID METAL CD

PROPERTY LINE

POINT OF TANGENT

PUBLIC UTILITY DISTRICT

POLYVINYL CHLORIDE

**#1 OF SNOHOMISH CNTY** 

REINFORCE(D)(MENT)(ING)


POUNDS PER SQUARE FOOT POUNDS PER SQUARE INCH

PLAN-BOAT RAMP SCALE: 1"=10'

SECTION/ELEVATION TITLE



SECTION/ELEVATION/DETAIL/VIEW LABELS



SECTION/ELEVATION/DETAIL/VIEW IDENTIFIERS

100% SUBMITTAL

REVISIONS DESIGNED BY: J. STRUB DESCRIPTION NO. DATE D. OLSEN CHECKED BY: W. AHN DATE: 05/23/25 PROJECT NO: 24-22-006

HEIGHT

HORIZ

HSE

INCL INFO INST

INSUL INT INV

KSF

LSH LT

LUMIN

HANDICAP

HORIZONTAL

HIGH POINT

HOUSE HEIGHT

HOT DIPPED GALV

INSIDE DIAMETER INVERT ELEVATION

INSIDE FACE

INCH/INCHES

INFORMATION

INSULATION

IRON PIPE

JOINT(S)

JUNCTION BOX

KIP (1,000 LB)

LENGTH, ANGLE

FOOT POUNDS

LINEAL FOOT/FEET

LONG SLOTTED HOLE

POUNDS

LIVE LOAD

LONGITUDINAL

LOW POINT

LEFT

LUMINAIRE


INTERIOR, INTERMEDIATE

KIPS PER SQUARE FOOT

KIPS PER SQUARE INCH

INCLÚDE

ISOLATION JOINT



VAULT

WITH

WOOD

WEIGHT WATER VALVE

WAREHOUSE

WORK POINT

YARD DRAIN

VERTICAL

WIDTH, WATER LINE, WEST

WATER METER, WATERMAIN

WELDED WIRE FABRIC

VAR VERT

WD

HORIZ NO SCALE IF "L" DOES NOT MEASURE 1" ADJUST

SCALES ACCORDINGLY



728 134th Street SW · Suite 200

SKAGIT COUNTY PARKS & RECREATION SWINOMISH CHANNEL BOAT LAUNCH RENOVATION

**G1.1** 

ABBREVIATIONS AND SYMBOLS Ph: 425 741-3800

CENTERLINE

COUNTY

COLUMN

COMMON

CONCRETE

CONTRACTOR

COORDINATE

CUBIC YARD

CYLINDER

DEGREE

DIAMETER

DIAGONAL

ANCHOR **DIMENSION** 

DIAPHRAGM

DEAD LOAD

DOWN SPOUT

DRIVEWAY DRAWING(S) DOWEL

DETAIL

CULVERT

CLEAN OUT

CLEAR(ANCE)

CAST IN PLACE CONSTRUCTION JOINT

CHAIN LINK FENCE

CORRUGATED METAL

CONC MASONRY UNIT

CONNECT, CONNECTION CONSTRUCT, CONSTRUCTION

CONTINUED/CONTINOUS

CENTER, CENTERED

DOUBLE DETECTOR

DEMOLISH, DEMOLITION

DRILLED-IN CONCRETE

CHECK VAVLE

DUCTILE IRON

CMP

CNTY

CO COL COM

CONC

CONN

CONT

CONST

CONTR

COORD

CTR

CULV

CY

CYL

DEG DET

DIA

DIAG

DIAPH

DICA

ALL TYPICAL DETAILS AND NOTES SHOWN ON THESE DRAWINGS ARE PART OF CONSTRUCTION CONTRACT AND SHALL BE PROVIDED. BY THE CONTRACTOR. TYPICAL DETAILS MAY NOT NECESSARILY BE INDICATED ON THE PLANS. BUT SHALL APPLY AS SHOWN OR DESCRIBED IN DETAILS.

THE NOTES SHALL BE USED ALONG WITH PROJECT SPECIFICATIONS AND DRAWINGS. REQUEST CLARIFICATION IMMEDIATELY UPON DISCOVER AND BEFORE PROCEEDING, WHERE A DIFFERENCE BETWEEN DRAWINGS, NOTES, OR SPECIFICATIONS OCCUR.

EXISTING CONDITIONS: CONTRACTOR SHALL VERIFY ALL ELEVATIONS, EXISTING DIMENSIONS, MEMBER SIZES, AND CONDITIONS PRIOR TO COMMENCING ANY WORK. ALL DIMENSIONS OF EXISTING CONSTRUCTION SHOWN ON THE DRAWINGS ARE INTENDED AS GUIDELINES ONLY AND MUST BE VERIFIED. EXISTING CONDITIONS SHOWN ON DRAWINGS ARE BASED EITHER ON SITE OBSERVATIONS, ORIGINAL DRAWINGS, OR WERE ASSUMED BASED ON EXPECTED CONDITIONS. IF EXISTING CONDITIONS DO NOT CLOSELY MATCH CONDITIONS SHOWN ON DRAWINGS, OR IF EXISTING MATERIALS ARE OF QUESTIONABLE OR SUBSTANDARD QUALITY, CONTRACTOR SHALL NOTIFY ENGINEER PRIOR TO COMMENCING ANY WORK.

CONTRACTOR RESPONSIBILITIES: DRAWINGS REPRESENT DESIGN IN COMPLETED FORM. CONTRACTOR SHALL BE RESPONSIBLE FOR METHODS. SEQUENCES. AND SAFETY PRECAUTIONS REQUIRED TO PERFORM WORK. CONTRACTOR SHALL PROTECT ALL EXISTING FEATURES NOT MARKED FOR DEMOLITION. CONTRACTOR SHALL CLEAN UP ALL AREAS AFFECTED BY CONSTRUCTION. CONTRACTOR SHALL PROVIDE TEMPORARY SHORING AND BRACING OF ALL STRUCTURAL MEMBERS. EXISTING CONSTRUCTION AND SOIL EXCAVATION AS REQUIRED. SHORING AND BRACING SHALL NOT BE REMOVED UNTIL ALL FINAL CONNECTIONS HAVE BEEN COMPLETED IN ACCORDANCE WITH DRAWINGS AND MATERIALS HAVE ACHIEVED DESIGN STRENGTH.

CONTRACTOR SHALL REVIEW AND STAMP SUBMITTALS PRIOR TO SUBMISSION, IF SHOP DRAWINGS DIFFER FROM DESIGN SHOWN ON STRUCTURAL DRAWINGS THEY SHALL BE SEALED BY WASHINGTON STATE REGISTERED PROFESSIONAL ENGINEER RESPONSIBLE FOR THE DESIGN. DIMENSIONS AND QUANTITIES ARE CONTRACTOR'S RESPONSIBILITY AND WILL NOT BE REVIEWED. CONTRACTOR SHALL BE RESPONSIBLE FOR ALL MATERIALS PLACED PRIOR TO RECEIPT OF SUBMITTAL. CONTRACTOR SHALL ALLOW MINIMUM OF 10 WORKING DAYS FOR REVIEW.

DISCREPANCIES: IN CASE OF DISCREPANCIES, CONTRACTOR SHALL NOTIFY THE ENGINEER OF DISCREPANCIES AND OBTAIN DIRECTION PRIOR TO PROCEEDING. NOTES ON INDIVIDUAL STRUCTURAL DRAWINGS SHALL TAKE PRIORITY OVER GENERAL NOTES. NOTED DIMENSIONS TAKE PRECEDENCE OVER SCALED DIMENSIONS. DO NOT SCALE DRAWINGS.

SPECIFICATIONS: REFER TO SPECIFICATIONS FOR INFORMATION IN ADDITION TO THESE NOTES AND DRAWINGS.

SPECIAL INSPECTION: PER IBC SECTIONS 1704 AND 1707, SHALL BE PERFORMED BY TESTING AGENCY ACCEPTABLE TO BUILDING OFFICIAL, AND AS OUTLINED IN SPECIAL INSPECTION SCHEDULE.

STRUCTURAL OBSERVATION: SHALL BE PERFORMED PER IBC 1709

SUBMITTALS: SHALL BE SUBMITTED FOR REVIEW PRIOR TO FABRICATION OR CONSTRUCTION IN ACCORDANCE WITH SPECIFICATIONS.

# <u>CODES</u>

ADA 2010 AMERICAN DISABILITIES ACT: ADA STANDARDS FOR ACCESSIBILITY DESIGN

ASCE/SEI 7-22 ASCE/ SEI: MINIMUM DESIGN LOADS & ASSOCIATED CRITERIA FOR BUILDINGS & OTHER STRUCTURES ACI 318-19

AMERICAN CONCRETE INSTITUTE: BUILDING CODE REQUIREMENTS FOR STRUCTURAL CONCRETE

IBC 2018 INTERNATIONAL BUILDING CODE: 2018 IBC CODE AND COMMENTARY

## <u>REFERENCES</u>

AISC 15 AMERICAN INSTITUTE OF STEEL CONSTRUCTION, STEEL CONSTRUCTION MANUAL 15TH EDITION ASCE MOP 50

ASCE MANUAL AND REPORTS ON ENGINEERING PRACTICE NO. 50, 3RD EDITION: PLANNING AND DESIGN

GUIDELINES FOR SMALL CRAFT HARBORS

AWS D1.1 AMERICAN WELDING SOCIETY: STRUCTURAL WELDING CODE - STEEL (2020)

UFC 4-152-01 UNIFIED FACILITIES CRITERIA: PIERS AND WHARVES

UFC 4-152-07 UNIFIED FACILITIES CRITERIA: DESIGN OF SMALL CRAFT BERTHING FACILITIES

MARINAS AND SMALL CRAFT HARBORS, 2ND EDITION, B.O. TOBIASSON & R.C. KOLLMEYER (2000)

UFC 4-159-03 UNIFIED FACILITIES CRITERIA: MOORINGS

DESIGN CRITERIA - BOARDING FLOAT

**BASIC:** 

A. FREEBOARD: MINIMUM 18 INCH AND MAXIMUM 30 INCH (UNDER DEAD LOAD ONLY) AND MINIMUM 12 INCH (UNDER FULL UNFACTORED LIVE LOAD PLUS DEAD LOAD)

STABILITY: BOARDING FLOATS SHALL BE STABLE UNDER ALL LOADING CONDITIONS. METACENTER SHALL BE LOCATED A SAFE DISTANCE ABOVE CENTER OF GRAVITY OF FLOATS. MAXIMUM TILTING OF DECK SHALL NOT EXCEED 0.10 INCHES PER FOOT OVER THE LONGITUDINAL LENGTH AND TRANSVERSE LENGTH OF EACH FLOAT MODULE.

#### B. DESIGN VESSEL

NAME	LENGTH	BEAM	DRAFT
	(FT)	(FT)	(FT)
DESIGN VESSEL	26	8.5	3

#### **DESIGN LOADS:**

BOARDING FLOATS MUST WITHSTAND THE LOAD CRITERIA AND COMBINATIONS LISTED BELOW.

LIVE LOADS

VERTICAL: 30 PSF (UNIFORMLY DISTRIBUTED) OR

300 LBS (CONCENTRATED POINT)

SNOW LOAD: 25 PSF

**ENVIRONMENTAL LOADS:** CURRENT SPEED: 4 KNOTS

WIND SPEED: 60 MPH

WIND-DRIVEN WAVE:

Hs: 2.0 FT SIGNIFICANT WAVE HEIGHT WITH 2.7 SEC WAVE PERIOD

BERTHING LOAD:

VESSEL APPROACH SPEED: 3.0 FT/SEC VESSEL APPROACH ANGLE: 10 DEGREES

#### LOAD COMBINATIONS - LRFD (LOAD RESISTANCE FACTOR DESIGN):

1.4D (DEAD)

1.2D (DEAD) + 1.6L (LIVE) + 0.5S (SNOW)

1.2D (DEAD) + 1.6S (SNOW) + L (LIVE)

1.2WV (WAVE) + C (CURRENT)

1.5BE (BERTHING)

LOAD COMBINATIONS - ASD (ALLOWABLE STRESS DESIGN):

D (DEAD)

D (DEAD) + L (LIVE)

D (DEAD) + S (SNOW)

D (DEAD) + 0.75L (LIVE) + 0.75S (SNOW)

WV (WAVE) + C (CURRENT)

BE (BERTHING)

### CONSTRUCTION NOTES

- 1. SUBMIT BALLAST AND INSTALLATION PLAN TO ENGINEER FOR APPROVAL PRIOR TO FLOAT FABRICATION.
- 2. DO NOT USE ANY LIQUID AS BALLAST.

## STRUCTURAL STEEL

STAINLESS STEEL BOLTS

UNLESS NOTED OTHERWISE, ALL STRUCTURAL STEEL ELEMENTS MUST BE HOT DIP GALVANIZED.

1. STEEL MATERIALS

SQUARE HOLLOW STRUCTURAL SECTION ASTM A500, GRADE B STEEL ANGLE ASTM A36 PLATES ASTM A36 PIPE ASTM A52, GRADE B MISCELLANEOUS STEEL ASTM A36 ASTM F3125, GRADE A325 STRUCTURAL BOLTS ASTM A563 NUTS WASHERS ASTM F436

STAINLESS STEEL NUTS & WASHERS ASTM F594, 316SS THRU-RODS A193 GRADE B8M CLASS 2 WITH A194 GRADE 8M NUTS & SS316 WASHERS

ASTM F593, 316SS

# **METAL** FABRICATION

- 1. SUBMIT ANY SHOP DRAWINGS IN ACCORDANCE WITH SPECIFICATION.
- 2. ALL WELDERS SHALL BE QUALIFIED IN ACCORDANCE WITH "STRUCTURAL WELDING CODE-STEEL (AWS D1.1). USE PROCEDURES, MATERIALS AND EQUIPMENT OF TYPE REQUIRED FOR THIS WORK.
- 3. PERFORM WELDING, WELDING INSPECTION, AND CORRECTIVE WELDING IN ACCORDANCE WITH "STRUCTURAL WELDING CODE-STEEL (AWS D1.1). USE CONTINUOUS WELDS ON ALL EXPOSED CONNECTIONS. GRIND VISIBLE WELDS AND CUT SURFACES SMOOTH IN FINISHED INSTALLATION. PROVIDE IN ACCORDANCE WITH SAFETY REQUIREMENTS OF "SAFETY AND HEALTH REQUIREMENTS MANUAL" (EM385-1-1).
- 4. WELDERS AND FABRICATION FACILITIES MUST BE WASHINGTON ASSOCIATION OF BUILDING OFFICIALS (WABO) CERTIFIED.
- 5. BOLTS, GRATING FASTENERS, WASHERS, HARDWARE, AND PARTS OR DEVICES NECESSARY FOR PROPER INSTALLATION MUST BE HOT DIP GALVANIZED, UNLESS INDICATED OTHERWISE. PROVIDE ISOLATION BETWEEN DISSIMILAR MATERIALS.

#### OTHER MATERIALS

PLASTIC LUMBER INTENDED FOR USE IN EXTERIOR APPLICATIONS MUST HAVE NO FADING OR DISCOLORATION AND NO CHANGE IN DIMENSIONAL STABILITY AS TESTED IN ACCORDANCE WITH ASTM D1435 FOR A PERIOD OF 5 YEARS.

COMPRESSIVE STRENGTH:

COMPRESSION PARALLEL TO GRAIN: 2,800 PSI MIN

COMPRESSION PERPENDICULAR TO GRAIN: 1.400 PSI MIN

FLEXURAL STRENGTH: 2.100 PSI

IMPACT RESISTANCE: 4.5 FT-LB/IN MIN

WATER ABSORPTION: < 0.1% IN 24 HOURS

PLASTIC TIMBER SHALL CONFORM TO THE FOLLOWING REQUIREMENTS:

- 1. MANUFACTURED WITH RECYCLED HDPE AND FIBERGLASS ELEMENTS
- 2. RESITANT TO UV AND SALT WATER
- RESISTANT TO IMPACT AND ABRASION
- 4. RESISTANT TO MARINE BORDERS
- ALL HARDWARE SHALL BE RECESSED FROM EXPOSED SURFACE OF PLASTIC LUMBER BY MINIMUM OF 1/2 INCH.

100% SUBMITTAL

REVISIONS DESIGNED BY: J. STRUB NO. DATE DESCRIPTION APP'D DRAWN RY D. OLSEN CHECKED BY: W. AHN DATE: 05/23/25 PROJECT NO: 24-22-006



HORIZ NO SCALE IF "L" DOES NOT MEASURE 1" ADJUST

SCALES ACCORDINGLY



Ph: 425 741-3800

SKAGIT COUNTY PARKS & RECREATION SWINOMISH CHANNEL BOAT LAUNCH RENOVATION

SHEET TITLE:

GENERAL NOTES

G1.2

## STRUCTURAL STEEL SPECIAL INSPECTION

SPECIAL INSPECTION FOR STRUCTURAL STEEL SHALL BE IN ACCORDANCE WITH AISC 341, AISC 360, AND FOLLOWING INFORMATION.

TASK - INDICATES WHETHER TO OBSERVE OR PERFORM (OR BOTH) INSPECTION TASK.

- DOC INSPECTOR SHALL PREPARE REPORTS INDICATING THAT WORK HAS BEEN PERFORMED IN ACCORDANCE WITH CONTRACT
- O OBSERVE THESE FUNCTIONS ON A RANDOM, DAILY BASIS, OPERATIONS NEED NOT BE DELAYED PENDING INSPECTIONS. FREQUENCY OF OBSERVATIONS SHALL BE ADEQUATE TO CONFIRM THAT WORK HAS BEEN PERFORMED IN ACCORDANCE WITH APPLICABLE DOCUMENTS.
- P PERFORM, FOR EACH JOINT OR MEMBER PRIOR TO FINAL ACCEPTANCE OF ITEM.
- QC TASKS INDICATED AS "QC" SHALL BE EXECUTED BY FABRICATOR AND ERECTOR IN ACCORDANCE WITH AISC 360 CHAPTER N QA TASKS INDICATED AS "QA" SHALL BE EXECUTED BY SPECIAL INSPECTOR IN ACCORDANCE WITH AISC 360 CHAPTER N.

## STEEL DETAILS

INSPECTION TASKS	QC	QA	REFERENCED STANDARD
INSPECT THE FABRICATED STEEL AND ERECTED STEEL FRAME TO VERIFY COMPLIANCE WITH THE DETAILS SHOWN ON THE CONSTRUCTION DOCUMENTS, SUCH AS BRACES, STIFFENERS, MEMBER LOCATIONS AND PROPER APPLICATION OF JOINT DETAILS AT EACH CONNECTION	0	0	AISC 360 CH. N

# WELDING

INSPECTION TASKS PRIOR TO WELDING	REFERENCED STANDARD	IBC REFERENCE		
INSPECTION TASKS PRIOR TO WELDING	QC	QA		
WELDING PROCEDURE SPECIFICATIONS (WPSS) AVAILABLE	Р	Р		
MANUFACTURER CERTIFICATIONS FOR WELDING CONSUMABLES AVAILABLE	Р	Р		
MATERIAL IDENTIFICATION (TYPE/GRADE)	0	0		
WELDER IDENTIFICATION SYSTEM 1	0	0		
FIT-UP OF GROOVE WELDS (INCLUDING JOINT GEOMETRY), JOINT PREPARATION, DIMENSIONS (ALIGNMENT, ROOT OPENING, ROOT FACE, BEVEL), CLEANLINESS (CONDITION OF STEEL SURFACES), TACKING (TACK WELD QUALITY AND LOCATION), BACKING TYPE AND FIT (IF APPLICABLE)	AISC 360 CH. N & AWS D1.1	1705.2.1		
CONFIGURATION AND FINISH OF ACCESS HOLES	0	0		
FIT-UP OF FILLET WELDS, DIMENSIONS (ALIGNMENT, GAPS AT ROOT), CLEANLINESS (CONDITION OF STEEL SURFACES), TACKING (TACK WELD QUALITY AND LOCATION)	0	0		
CHECK WELDING EQUIPMENT	0	_		
INSPECTION TASKS DURING WELDING			REFERENCED STANDARD	IBC REFERENCE
INSPECTION TASKS DURING WELDING	QC	QA		
USE OF QUALIFIED WELDERS	0	0		
CONTROL AND HANDLING OF WELDING CONSUMABLES, PACKAGING, EXPOSURE CONTROL	0	0		
NO WELDING OVER CRACKED TACK WELDS	0	0		
ENVIRONMENTAL CONDITIONS, WIND SPEED WITHIN LIMITS, PRECIPITATION AND TEMPERATURE	0	0	AISC 360 CH. N & AWS D1.1	1705.2.1
WPS FOLLOWED, SETTINGS ON WELDING EQUIPMENT, TRAVEL SPEED, SELECTED WELDING MATERIALS, SHIELDING GAS TYPE/FLOW RATE, PREHEAT APPLIED, INTERPASS TEMPERATURE MAINTAINED (MIN / MAX), PROPER POSITION (F, V, H, OH)	0			
WELDING TECHNIQUES, INTERPASS AND FINAL CLEANING, EACH PASS WITHIN PROFILE LIMITATIONS, EACH PASS MEETS QUALITY REQUIREMENTS	0			
INSPECTION TASKS AFTER WELDING			REFERENCED STANDARD	IBC REFERENCE
INSPECTION TASKS AFTER WELDING	QC	QA		
WELDS CLEANED	0	0		
SIZE, LENGTH AND LOCATION OF WELDS	Р	Р		
WELDS MEET VISUAL ACCEPTANCE CRITERIA, CRACK PROHIBITION, WELD / BASE-METAL FUSION, CRATER CROSS SECTION, WELD PROFILES, WELD SIZE, UNDERCUT, POROSITY	Р	Р	AISC 360 CH. N	
ARC STRIKES	Р	Р	& AWS D1.1	1705.2.1
K-AREA <sup>2</sup>	Р	Р		
BACKING REMOVED AND WELD TABS REMOVED (IF REQUIRED)	Р			
REPAIR ACTIVITIES	Р	Р		
DOCUMENT ACCEPTANCE OR REJECTION OF WELDED JOINT OR MEMBER	Р	Р		

- 1. FABRICATOR OR ERECTOR, AS APPLICABLE, SHALL MAINTAIN SYSTEM BY WHICH WELDER WHO HAS WELDED JOINT OR MEMBER CAN BE IDENTIFIED. STAMPS, IF USED, SHALL BE LOW-STRESS TYPE.
- 2. WHEN WELDING OF DOUBLER PLATES, CONTINUITY PLATES OR STIFFENERS HAS BEEN PERFORMED IN k-AREA, VISUALLY INSPECT WEB k-AREA FOR CRACKS WITHIN 3 INCHES OF WELD.

# **BOLTING**


INSPECTION TASKS PRIOR TO BOLTING			REFERENCED STANDARD	IBC REFERENCE	
INSPECTION TASKS PRIOR TO BOLTING	QC	QA			
MANUFACTURER'S CERTIFICATIONS AVAILABLE FOR FASTENER MATERIALS	0	Р			
FASTENERS MARKED IN ACCORDANCE WITH ASTM REQUIREMENTS	0	0			
PROPER FASTENERS SELECTED FOR THE JOINT DETAIL (GRADE, TYPE, BOLT LENGTH IF THREADS ARE TO BE EXCLUDED FROM SHEAR PLANE)	0	0			
PROPER BOLTING PROCEDURE SELECTED FOR JOINT DETAIL	0	0	AISC 360 CH. N	1705.2.1	
CONNECTING ELEMENTS, INCLUDING THE APPROPRIATE FAYING SURFACE CONDITION AND HOLE PREPARATION, IF SPECIFIED, MEET APPLICABLE REQUIREMENTS	0	0			
PRE-INSTALLATION VERIFICATION TESTING BY INSTALLATION PERSONNEL OBSERVED AND DOCUMENTED FOR FASTENER ASSEMBLIES AND METHODS USED	Р	0			
PROPER STORAGE PROVIDED FOR BOLTS, NUTS, WASHERS AND OTHER FASTENER COMPONENTS	0	0			
INSPECTION TASKS DURING BOLTING	REFERENCED STANDARD	IBC REFERENCE			
INSPECTION TASKS DURING BOLTING	QC	QA			
FASTENER ASSEMBLIES, OF SUITABLE CONDITION, PLACED IN ALL HOLES AND WASHERS (IF REQUIRED) ARE POSITIONED AS REQUIRED	0	0		1705.2.1	
JOINT BROUGHT TO THE SNUG-TIGHT CONDITION PRIOR TO THE PRETENSIONING OPERATION	0	0	AISC 360 CH. N		
FASTENER COMPONENT NOT TURNED BY THE WRENCH PREVENTED FROM ROTATING		0			
FASTENERS ARE PRETENSIONED IN ACCORDANCE WITH THE RCSC SPECIFICATION, PROGRESSING SYSTEMATICALLY FROM THE MOST RIGID POINT TOWARD THE FREE EDGES	0	0			
INSPECTION TASKS AFTER BOLTING			REFERENCED STANDARD	IBC REFERENCE	
INSPECTION TASKS AFTER BOLTING	QC	QA	AICC 7CO CIL N	1705.0.1	
DOCUMENT ACCEPTANCE OR REJECTION OF BOLTED CONNECTIONS	Р	Р	AISC 360 CH. N	1705.2.1	

100% SUBMITTAL

SHEET NO.

REVISIONS DESIGNED BY: J. STRUB APP'D DRAWN BY: NO. DATE DESCRIPTION D. OLSEN CHECKED BY: W. AHN DATE: 05/23/25 PROJECT NO: 24-22-006







SHEET TITLE:

